

ST600P

CONN	PIN	COLOR	OUTPUT	AWG	LENGTH	
P1B	1	ORANGE	+3.3V	18	500.0 ± 25.0	
	2	ORANGE	+3.3V			
	3	BLACK	GND			
	4	RED	+5V			
	5	BLACK	GND			
	6	RED	+5V			
	7	BLACK	GND			
	8	GRAY	PG			22
	9	PURPLE	+5VSB			18
	10	YELLOW	+12V			18
	11	YELLOW	+12V			
	12	ORANGE	+3.3V			
	13	ORANGE	+3.3Vs	22		
	14	BLUE	-12V	18		
	15	BLACK	GND	18		
	16	GREEN	PS-DN			22
	17	BLACK	GND			
	18	BLACK	GND			
	19	BLACK	GND	18		
	20	NC	NC			NC
	21	RED	+5V			500.0 ± 25.0
	22	RED	+5V			
	23	RED	+5V			
	24	BLACK	GND			
P2B	1	BLACK	GND	18	750.0 ± 25.0	
	2	BLACK	GND			
	3	BLACK	GND			
	4	BLACK	GND			
	5	YELLOW	+12V			
	6	YELLOW	+12V			
	7	YELLOW	+12V			
	8	YELLOW	+12V			
P2B-1	1	BLACK	GND	18	150.0 ± 12.0	
	2	BLACK	GND			
	3	BLACK	GND			
	4	BLACK	GND			
	5	YELLOW	+12V			
	6	YELLOW	+12V			
	7	YELLOW	+12V			
	8	YELLOW	+12V			
P2D	1	YELLOW	+12V	18	500.0 ± 25.0	
	2	YELLOW	+12V			
	3	YELLOW	+12V			
	4	BLACK	GND			
	5	BLACK	GND			
	6	BLACK	GND			
	7	BLACK	GND			
	8	BLACK	GND			
P2D-1	1	YELLOW	+12V	18	150.0 ± 12.0	
	2	YELLOW	+12V			
	3	YELLOW	+12V			
	4	BLACK	GND			
	5	BLACK	GND			
	6	BLACK	GND			
	7	BLACK	GND			
	8	BLACK	GND			

CONN	PIN	COLOR	OUTPUT	AWG	LENGTH
PD	1	YELLOW	+12V	18	500.0 ± 25.0
	2	BLACK	GND		
	3	BLACK	GND		
	4	RED	+5V		
PE PH	1	YELLOW	+12V	22	150.0 ± 12.0
	2	BLACK	GND		
	3	BLACK	GND		
	4	RED	+5V		
PF	1	RED	+5V	22	500.0 ± 25.0
	2	BLACK	GND		
	3	BLACK	GND		
	4	YELLOW	+12V		
P5 P5-2	1	YELLOW	+12V	20	500.0 ± 25.0
	2	BLACK	GND		
	3	RED	+5V		
	4	BLACK	GND		
	5	ORANGE	+3.3V		
P5-1 P5-3	1	YELLOW	+12V	20	150.0 ± 12.0
	2	BLACK	GND		
	3	RED	+5V		
	4	BLACK	GND		
	5	ORANGE	+3.3V		

