




**SILVERSTONE**<sup>®</sup>  
Designing Inspiration



## 5.25" USB 3.1 Gen 1 multi-card reader with four power metered USB ports and fan controller

# FP59

- Fits in any 5.25" external drive bay
- Integrated display for monitoring voltage and current
- 5-slot all-in-one card reader supports CF / SD / XD / MS / TF / M2 cards
- Three USB 3.1 Gen 1 HUB (Type-A x 2, Type-C x 1) and one fast charging port up to 5V/2A
- Adjustable fan speed controller for 3pin fan
- Compliant with USB battery charging specification 1.2



5-slot all-in-one card reader supports CF / SD / XD / MS / TF / M2 cards



Three USB 3.1 Gen 1 HUB (Type-A x 2, Type-C x 1) and one fast charging port up to 5V/2A



Integrated display for monitoring voltage and current



Adjustable fan speed controller for 3pin fan

## Specifications

Model No.	SST-FP59B
Color	Black
Material	Aluminum & plastic
Controller	GL3522, GL3223, MA5887
Application	5.25" drive bay
Indicator	Solid green : power on Blinking red : read / write. (for card reader)
Interface	USB 3.1 Gen 1 (5Gbps) (Compatible with USB 2.0 / 1.1)
USB ports	USB 3.1 Gen 1 Type-C x 1, Type-A x 2 USB Type-A with dedicated charging port x 1, up to 5V/2A
Media card support	USB / SDHC / SDXC / Mini SD / Micro SD (T-Flash) / MS / MS Duo / MS PRO / MS PRO Duo / MS Micro (M2) / MS PRO-HG Duo / MS PRO-HG Duo / MS PRO-HG Duo HX / MMC / RS- MMC / MMC Micro / MMC Mobile / xD / CF

Detect range	Voltage : 0-5.5V tolerance $\pm$ 0.1V Current : 0-2.5A tolerance $\pm$ 0.1A
Temperature	Operating : 0°C ~ 65°C Storage : 0°C ~ 65°C
Humidity	Operating : 10% ~ 90% Storage : 5% ~ 95%
Fan connector	3pin x 1
Fan voltage range	5.5V ~ 12V
Fan max. output	3A
Operating system support	Microsoft Windows 10/8.1/8/7/Vista (32-bit or 64-bit) or future release versions. Linux and MAC OS X
Net Weight	125 $\pm$ 10g
Dimension	148mm (W) x 42mm (H) x 70mm (D) 5.83" (W) x 1.65" (H) x 2.76" (D)

### Taiwan Headquarters

12F., No.168, Jiankang Rd.,  
Zhonghe Dist., New Taipei City 235,  
Taiwan R.O.C.

Tel: + 886-2-8228-1238 / Fax: + 886-2-8228-7123  
For sales and purchasing: sales@silverstonetek.com

### USA

13626 Monte Vista Ave. Unit #A,  
Chino, CA 91710,  
USA

Tel: + 1-909-465-9596 / Fax: + 1-909-465-9569  
For General Questions/Sales: usasales@silverstonetek.com

### Europe

Brandstücken 27,  
D-22549 Hamburg,  
Germany

Tel: + 49-40-675931-0 / Fax: + 49-40-675931-66  
For sales and purchasing: sales.eu@silverstonetek.de