

# SX300







Small in size, Big on power



- Support standard SFX form factor
- 24/7 continuous power output with 40°C operating temperature
- Silent running 80 mm fan with 18dBA minimum
- High efficiency with 80 PLUS Bronze certification
- Class-leading single +12V rail
- PCIe 8pin and PCIe 6pin connectors support

## SPECIFICATIONS

Model No.	SST-SX300-B
Color	Black (Lead-Free Paint)
MTBF	100,000 hours
Operating temperature	0 ~ 40°C
Cooling System	Single 80mm silent fan
Noise Level	18dBA minimum
Dimension	125 mm (W) x 63.5 mm(H) x 100 mm(D) 4.92" (W) x 2.5" (H) x 3.94" (D)

Photo	Type	Connector quantity	Cable quantity	Length
	MB 24/20P connector	1	1	300mm
	CPU 4+4P connector	1	1	400mm
	PCI-E 6+2P connector	2	1	400mm 150mm
	SATA connector	3	1	300mm 200mm 100mm
	Peripheral 4P connector	2	1	100mm
	Floppy 4P connector	1	1	300mm 200mm

**24/7 continuous power output with 40°C operating temperature**



### **Support IEC 62368-1 safety standard**

Comply with updated safety standard to provide additional security for you under the changing regulations



### **Active PFC + Forward + DC to DC design**

Active PFC provides higher power efficiency, while Forward + DC to DC design provides stability and reliability

**Enables impressively small form factor builds**

